

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**
- Article number: 311100
- UFI: 4KE0-J0FQ-V007-6U9E
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
SU3 Industrial uses: use of substances as such or in preparations in an industrial environment
SU22 Professional use: Public domain (administration, education, entertainment, services, craftsmen)
- Application of the substance / the mixture Degreaser
- Uses advised against SU21 Consumer use: Private households / general public / consumers
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Inter-Che-M B.V.
Platinawerf 22-26,
6641TL Beuningen
Holland
T +31 (0)24 678 02 20
E sds@interchem.nl
W www.interchem.nl
- Further information obtainable from: Product safety department: sds@interchem.nl
- 1.4 Emergency telephone number:
Intended only to inform doctors in case of accidental poisoning.
National Poisoning Information Centre - Bilthoven
T +31 (0)88 755 8000

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 1)

· Hazard pictograms



GHS02

GHS07

GHS08

GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

· Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

* SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components %(m/m):

EC number: 920-750-0 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics 75-100%

Reg.nr.: 01-2119473851-33 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336, EUH066

CAS: 141-78-6 ethyl acetate ≥2.5-<10%

EINECS: 205-500-4 ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066

Reg.nr.: 01-2119475103-46

CAS: 110-82-7 cyclohexane ≥0.5-<2.5%

EINECS: 203-806-2 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic

Reg.nr.: 01-2119463273-41 Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 2)

- After eye contact:
Rinse opened eye for several minutes under running water. Then consult a doctor.
Contact lens removal.
- After swallowing:
Rinse mouth.
Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

* SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2 or powder. Fight larger fire with alcohol-resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Carbon monoxide (CO)
- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

* SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Collect leaking liquid in sealable waste containers.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles:
Store in a cool location.
Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

— EU —
(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 3)

* SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm

110-82-7 cyclohexane

IOELV Long-term value: 700 mg/m³, 200 ppm

- DNELs

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Dermal	Long-term exposure - systemic effects	773 mg/kg bw/day (worker) ECHA database
Inhalative	Long-term exposure - systemic effects	2,035 mg/m ³ (worker) ECHA database

141-78-6 ethyl acetate

Dermal	Long-term exposure - systemic effects	63 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	1,468 mg/m ³ (worker)
	Acute - short-term exposure - local effects	1,468 mg/m ³ (worker)
	Long-term exposure - systemic effects	734 mg/m ³ (worker)
	Long-term exposure - local effects	734 mg/m ³ (worker)

110-82-7 cyclohexane

Dermal	Long-term exposure - systemic effects	2,016 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	700 mg/m ³ (worker)
	Acute - short-term exposure - local effects	700 mg/m ³ (worker)
	Long-term exposure - systemic effects	700 mg/m ³ (worker)
	Long-term exposure - local effects	700 mg/m ³ (worker)

- PNECs

141-78-6 ethyl acetate

PNEC 0.115 mg/kg (sediment marine water)
1.15 mg/kg (sediment freshwater)
0.148 mg/kg (soil)
PNEC 650 mg/l (STP)
0.24 mg/l (aqua, freshwater)
1.65 mg/l (aqua, intermittent releases)
0.024 mg/l (aqua, marine water)

110-82-7 cyclohexane

PNEC 2.99 mg/kg (bd)
3.627 mg/kg (sediment)
PNEC 0.207 mg/l (aqua, freshwater)
0.207 mg/l (aqua, marine water)
0.207 mg/l (periodiek vrijkomen)
3.24 mg/l (STP)

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls Ensure adequate ventilation.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

• **Respiratory protection:**

Short term filter device:

Filter type A.

If workers are exposed to concentrations above the exposure limit, they should use a suitable, certified respirator.

• **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

Suitable material for safety gloves (EN 374):

Nitrile rubber, NBR

• **Penetration time of glove material**

Permeation value: Level ≥ 480 min (hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycene)

Thickness of gloves ≥ 0.5 mm (Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye/face protection**



Tightly sealed goggles

• **Body protection:** Solvent resistant protective clothing

• **Environmental exposure controls** No additional data. See 6 and 13.

* SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **General Information**

• **Physical state**

Fluid

• **Colour:**

Clear

• **Odour:**

Characteristic

• **Odour threshold:**

Not determined.

• **Melting point/freezing point:**

Undetermined.

• **Boiling point or initial boiling point and boiling range** ≥ 90 - ≤ 165 °C (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

Highly flammable.

• **Flammability**

• **Lower and upper explosion limit**

• **Lower:**

Not determined.

• **Upper:**

Not determined.

• **Flash point:**

3 °C

• **Decomposition temperature:**

Not determined.

• **pH**

Not determined.

• **Viscosity:**

• **Kinematic viscosity at 20 °C**

0.76 mm²/s

• **Dynamic:**

Not determined.

• **Solubility**

• **water:**

Slightly soluble.

• **Partition coefficient n-octanol/water (log value)**

Not determined.

• **Vapour pressure at 20 °C:**

≤ 35 hPa (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

• **Vapour pressure at 50 °C:**

≤ 120 hPa

• **Density and/or relative density**

• **Density at 20 °C:**

0.74 g/cm³

• **Relative density**

Not determined.

(Contd. on page 6)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 5)

· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	100.0 %
· VOC (EC)	740.0 g/l 100.00 %
· Solids content:	0.0 %
· Molecular weight	113 g/mol
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidizing agents.
- 10.4 Conditions to avoid High temperatures
- 10.5 Incompatible materials:
 - Strong oxidising products.
 - Rubber
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 6)

· LD/LC50 values relevant for classification:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral LD50 >2,000 mg/kg (rat)
 Dermal LD50 >2,000 mg/kg (rabbit)
 Inhalative LC50/4h >23.3 mg/l (rat)

141-78-6 ethyl acetate

Oral LD50 4,934 mg/kg (rabbit) (OECD 401)
 Dermal LD50 5,620 mg/kg (rat)
 >20,000 mg/kg (rabbit)
 Inhalative LC50/4h 29.3 mg/l (rat)

110-82-7 cyclohexane

Oral LD50 12,705 mg/kg (rat)
 Dermal LD50 >2,000 mg/kg (rabbit) (OESO 402)
 Inhalative LOAEL/4h 20 mg/l (rat) (OESO 403)
 NOAEL/90d 250 ppm (rat)
 LC50/4h >32.88 mg/l (rat) (OESO 403)

· Primary irritant effect:

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

* SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

EL50/48h 3 mg/l (daphnia magna)

141-78-6 ethyl acetate

NOEC/32d 9.65 mg/l (pimphales promelas)
 <9.65 mg/l (fish)
 NOEC/21d 2.4 mg/l (daphnia magna)
 EC50/48h 610 mg/l (daphnia magna)
 5,600 mg/l (desmodesmus supspicatus)
 LC50/96h 230 mg/l (pimphales promelas)

110-82-7 cyclohexane

EC50/96h 4.53 mg/l (fish) (OESO 203)
 NOEC/72h 0.94 mg/l (algae)
 EC50/48h 2.4 mg/l (daphnia magna)
 EC50/72h 9.317 mg/l (algae)

- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 7)

- Degree of elimination:

141-78-6 ethyl acetate

OESO 303A >99.9 % (/) (OESO 303A)
(readily biodegradable)

- Other information: The product is easily biodegradable.
- 12.3 Bioaccumulative potential

141-78-6 ethyl acetate

BCF 30 /3d (/)

LogPow 0.68 (/)

- 12.4 Mobility in soil

141-78-6 ethyl acetate

Koc 1.43 (/)

- 12.5 Results of PBT and vPvB assessment

- PBT: Not applicable.

- vPvB: Not applicable.

- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects

- Remark: Toxic for fish

- Additional ecological information:

- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

* SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

07 01 04* other organic solvents, washing liquids and mother liquors

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number

- ADR/ADN, IMDG, IATA

UN1263

- 14.2 UN proper shipping name

- ADR/ADN

1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY
HAZARDOUS

- IMDG

- IATA

PAINT RELATED MATERIAL, MARINE POLLUTANT
PAINT RELATED MATERIAL

- 14.3 Transport hazard class(es)

- ADR/ADN, IMDG



- Class

3 Flammable liquids.

(Contd. on page 9)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 8)

· Label

3

· IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· ADR/ADN, IMDG, IATA

II

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances:
HYDROCARBONS, C7-C9 N-ALKANES, ISO-ALKANES, CYCLICS

· Marine pollutant:

Yes

· Special marking (ADR/ADN):

Symbol (fish and tree)

· 14.6 Special precautions for user

Symbol (fish and tree)

· Hazard identification number (Kemler code):

Warning: Flammable liquids.

· EMS Number:

33

· Stowage Category

F-E, S-E

· 14.7 Maritime transport in bulk according to IMO instruments

B

Not applicable.

· Transport/Additional information:

· ADR/ADN

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1263 PAINT RELATED MATERIAL, 3, II, ENVIRONMENTALLY
HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 57

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar standaard**

(Contd. of page 9)

- REGULATION (EU) 2019/1148
- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
 - None of the ingredients is listed.
- Annex II - REPORTABLE EXPLOSIVES PRECURSORS
 - None of the ingredients is listed.
- Regulation (EC) No 273/2004 on drug precursors
 - None of the ingredients is listed.
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
 - None of the ingredients is listed.
- National regulations:
- Other regulations, limitations and prohibitive regulations

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- Classification according to Regulation (EC) No 1272/2008

Flammable liquids

Bridging principles

Specific target organ toxicity (single exposure)
Hazardous to the aquatic environment - long-term (chronic)
aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Aspiration hazard

Expert judgement

- Department issuing SDS: Product safety department.
- Date of previous version: 08.05.2023
- Version number of previous version: 10
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

(Contd. on page 11)

— EU —

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.03.2025

Version number 11 (replaces version 10)

Revision: 22.11.2024

Trade name: **TD10 Ontvetter kort / Silicon Remover D6 / Siliconen verwijderaar
standaard**

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

• * Data compared to the previous version altered.

— EU —