



Technical Data Sheet

Date of issue: 08/09/2021

Date of update: 08/09/2021

Version: 1

FOAM MASKING TAPE

P/N: 39273 (SAP No. 300003671) 13 mm x 20 m

91056 (SAP No. 300008840) 13 mm x 50 m

Product overview:

The extremely soft and elastic foam masking tape is intended for the masking of gaps around the door, hood and trunk panels. The product provides a smooth transition of the applied coats around the edges and body stampings. The product effectively prevents penetration of overspray into the vehicle. Thanks to its high elasticity, it easily conforms to profiles and rounded edges. The product has excellent adhesion and leaves no adhesive residues when peeled off.

Characteristics:

- Eliminates sharp coating edges
- Prevents penetration of overspray into the vehicle
- Easy to apply and flexible
- Resistant to continuous high temperatures (up to 80°C)
- Intended for processing with water-borne and solvent coating products

Technical data:

	Value
Material:	Polyurethane ester foam; adhesive: PSA
Colour:	white
Density:	24-27 kg/m ³
Rigidity at 40%:	3.4-4.6 kPa
Tensile strength:	>250 kPa
Ultimate elongation:	>180%
Permanent deformation:	<20%
Cell/pore size:	500-625 µm
Tape width:	13 mm
Roll length:	20 or 50 m

Application requirements, shelf life, and storage:

Carefully clean, remove dust, and degrease the substrate to which the tape will be applied. Use at temperatures between +10°C and +25°C. Apply and press down onto the surface. Peel off the tape in one smooth move, without tearing forcibly or pulling sharply.

The product will perform best for 12 months from the production date if stored in its original container, in a dry location between +10°C and +25°C. Keep away from direct heat and sunlight; protect from frost.

Please note:

The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to perform a test application of the product due to its potentially different reaction with different materials. We cannot be held liable for defects where the final results were affected by factors beyond our control. NOVOL reserves the right to improve the product and modify the technical requirements, which may entail modification of the specification. This product is not hazardous if used as intended.

NOVOL Sp. z o.o., ul. Żabikowska 7/9, PL 62-052 Komorniki, tel. +48 61 810 98 00, novol.com